



REVISIONS		
REV	DESCRIPTION	APPROVED



- NOTES:
- MOLDED CONNECTOR END REQUIREMENTS:
 - A. INNER MOLD USING PE
 - B. ALUMINUM FOIL WRAP TO CONNECTOR
 - C. PVC - 45P BLACK
 - CABLE: [28AWG (7/0.12)*15C+AL/MY +DW(7/0.12)]TIN
 COLOR: P1 COLOR CODE
 JACKET: PVC $\varnothing=6.0\pm 0.15\text{mm}$
 COLOR: BLACK
 - FINISHED PRODUCTS LENGTH:
 (1) LFNGTH= 305 mm

PIN		OUTS		COLOR	
HD 15M	HD 15M	HD 15M	HD 15M	HD 15M	HD 15M
1	1	YELLOW	9	9	ORANGE
2	2	PINK	10	10	PURPLE
3	3	YELLOW-BLACK	11	11	BLUE
4	4	WHITE	12	12	GREEN
5	5	BLACK	13	13	LIGHT-BLUE
6	6	RED - BLACK	14	14	GRAY
7	7	RED	15	15	BROWN
8	8	ORANGE-BLACK	Shell	Shell	

ITEM NO	PART NAMES	Q'TY	REMARK
5	(SCREW)NUT:4.75*6mm NICKEL-PLATING	2PCS	
4	THUMBSCREW: MALE 4*47mm NICKEL-PLATING	4PCS	
3	CONNECTOR:HD15P MALE NICKEL-PLATING, INSULATOR COLOR:BLUE	1PCS	
2	CONNECTOR:HD15P MALE NICKEL-PLATING, INSULATOR COLOR:BLUE	1PCS	
1	CABLE:15C+1 28AWG COLOR:BLACK	1PCS	

PRODUCT	HD15PMALE TO HD15P MALE	CUSTOMER		DRAWN	Hvon .W	
CUS,NO	00607	VERSION		CHECKED	Jackson H	
DR,NO	SD130-XXX	DRAWN DATE	DEC.21.2002	APPROVED		