



PIN		OUTS	
A		B	
1	—	1	
6	—	2	
2	—	3	
7	—	4	
3	—	5	
8	—	6	
4	—	7	
9	—	8	
5	—	9	
NC	—	10	

TEST CONDITION: LOW-VOLTAGE 15V			
INSULATION: UPON 1M ohm			
ELECTRIC CONDUCTION:INSIDE 1.5K ohm			
6	BRACKET:(D-SUB 9P) L- COMMON TYPE	1PCS	
5	HEX SCREWS: 4-40UNC 4.8*11.8*2.75mm	2PCS	
4	DKN:(D-SUB 9P 09*09*) BLACK WITH NUT	1PCS	
3	CONNECTOR:DB9M BLACK SOLDER TYPE PIN:G/F, INSULATOR COLOR:BLACK	1PCS	
2	CONNECTOR:PITCH 2.54*2.54mm IDC 10P SOCKET (HAVE THREE/NO SR),BLACK	1PCS	
1	CABLE:UL2651 28AWG 9C FLAT CABLE GRAY PITCH:1.27mm 307mm	1PCS	
ITEM NO	DESCRIPTION	Q'TY	REMARK

PCCABLES.COM INC pccables.com/products/07121.html	PRODUCT	DB9M to IDC 10pin cable	CUSTOMER	PCCABLES	DRAWN	z.q.h	 THREE ANGLE PROJECTION
	CUS,NO	07121	VERSION	1	CHECKED		
	DR,NO		DRAWN DATE	2009.03.05	APPROVERD		