


1	RED
2	WHITE
3	GREEN
4	BLACK
5	SHELL

PCB  
USL-100



**NOTES:**  
 1. CABLE:[28AWG(7/0.127)\*1P+28AWG(7/0.127)\*2C+AL/MY+DW(7/0.127)+65%BD(16/5/0.1)]TIN INSULATION WIRE ONE:FO-PE,OD=∅0.84±0.03MM COLOR: WHITE&GREEN INSULATION WIRE TWO:SR-PVC,OD=∅0.84±0.03MM COLOR:BLACK,RED JACKET:80°C 80P PVC OD=∅3.80±0.10MM FINISHED PRODUCTS LENGTH:  
 (1) LENGTH=1FT TOLERANCE:±25.4mm

PIN OUTS		
DB 9P M+PCB(P1)	WIRE COLOR	USB A M(P2)
1	RED	1
4	BLACK	4
2	WHITE	2
3	GREEN	3
SHELL		SHELL

INSULATION: UPON 1M ohm AND 1M ohm ELECTRIC CONDUCTION:INSIDE 1.5K ohm				
ITEM NO	PART	NAMES	QTY	REMARK
5		BLACK SHELL PRINTING" GOLDX" ONLY" GOLD" IS GOLD THE OTHERS COLOR IS WHITE.	1SET	
4		THUMBSCREW: 4* 66mm PLATE WITH GOLD , COLOR : PANTONE#322C 45P PVC	2PCS	
3		CONNECTOR: USB AM , PIN : G/F , COLOR : PANTONE#426C 45P PVC. (871C) "X" ON BOTH SIDES.	1PCS	
2		CONNECTOR: DB 9P M ,INSULATOR COLOR: PANTONE#322C	1PCS	
1		CABLE: 1P 28AWG; 2C 28AWG, JACKET: BLACK	1PCS	

<b>PCCABLES.COM</b> https://www.pccables.com	PRODUCT	USB AM TO PCB	CUSTOMER	PCCABLES	DRAWN		
	CUS,NO	70707 and 70708	VERSION	1	CHECKED	DJ	
	DR,NO	SDGXMU-1201	DRAWN DATE	2021-AUG-10	APPROVERD	JACKY	

THREE ANGLE PROJECTIO