



NOTES:

1. MATERIALS

1.1 CABLE: [7/0. 12BCX1P+7/0. 20BCX2C+AM+7/0. 12BC+B(16/3/0. 12ALM)+BLACK PVC JACKET.

OD=∅4.5±0.15MM.

CABLE MARKING:USB 2.0 CABLE FULLY RATED 30V 80°C

1.2 CONNECTOR: P1: USB A TYPE MALE: SOLDER TYPE, WHITE PBT INSULATION, GOLD FLASH CONTACTS, GOLD PLATED SHELL.

1.3 P2: USB2.0 A TYPE FEMALE: SOLDER TYPE, WHITE PBT INSULATION, GOLD FLASH CONTACTS, GOLD PLATED SHELL, SHEATH OF IRON NICKEL PLATING.

1.4 ALL HOOD: MOLDED BLACK PVC.

2. 100% OPEN AND SHORT TEST.

3. PACKING: 1PCS/PE BAG.

4. ALL MATERIAL BE RoHS COMPLIANT.

PIN OUT

P1 ——— P2

1 ——— 1 RED

2 ——— 2 WHITE

3 ——— 3 GREEN

4 ——— 4 BLACK

SHELL ——— SHELL (BRAID+DRAIN)

⊗ > PAIR

LENGTH TOLERANCE: X. ± 0.5 .X ± 0.2 .XX ± 0.1		SCALE: FREE	CUS. NAME:		ENG:	
ANGLE TOLERANCE: X° ± 3° .X° ± 1°		UNIT: mm	VERSION: 00		PRODUCT NO:	CUSTOMER NO: PCC71511
REV.		DATE	PAGE: 1/1		DRAWING NO:	PRODUCT DESCRIPTION: USB2.0 AM/AF
NEW ISSUE		MODIFY DESCRIPTION		CHECKED:		APPROVED: