


1. Electrical test:

- (1). 100% OPEN SHORT & MISS WIRE TEST;
- (2). INSULATION RESISTANCE:DC 250V 3MOHM Min;
- (3). CONTACTOR RESISTANCE:5 OHM Max;



2. FINISHED PRODUCTS LENGTH:
87050 GFT LENGTH=1829 ± 25.4mm

PIN
OUT
P1:DB9F P2:3.5S MALE

- 1-6-7-8
- 2 ——— Tip-Left
- 3 ——— Ring-Right
- 4
- 5 ——— shield-Ground
- 9

4	THUMBSCREW: 4*47mm MALE, NICKEL-PLATING BOOT COLOR:BLACK	2PCS	
3	CONNECTOR: DB9PIN FEMALE,NICKEL-PLATING BOOT COLOR:BLACK	1PCS	
2	CONNECTOR: 3.5S MALE,GOLD-PLATING BOOT COLOR:BLACK	1PCS	
1	CABLE: 7/0.12TA+2C+2A JACKET: PVC	1PCS	
NO	CD: 3.5 ± 0.15mm, COLOR:BLACK		
	PART NAME	QTY	REMARK

Change
Details

	NAME	DB9F FEMALE-3.5s MALE	CUSTOMER	PCCABLES	DRAWN
	CUS	PCC87050	VERSION	1	CHECKED
	DR, NO		DRAWN DATE	2011.02.21	APPROVED