



- NOTES:
1. INNER MOLDED BY PE, OUTER MOLDED BY 45P BLACK PVC.
  2. CABLE: [28AWG(7/0.127)\*1P+28AWG(7/0.127)\*2C+ FILLER +AL/MY+DW(7/0.127)+BD(16/5/0.10)]TIN
- INSULATION: 1P: HD-PE, OD=Ø0.80±0.05mm,  
 COLOR: WHITE, GREEN  
 2C: SR-PVC, OD=Ø0.85±0.05mm,  
 COLOR: RED, BLACK  
 JACKET: PVC OD=Ø3.8±0.15mm  
 JACKET COLOR: TRANSPARENT

PIN		OUTS	
USB A MALE	MINI BSP MALE	WIRE COLOR	
1	1	RED	
2	2	WHITE	
3	3	GREEN	
4	5	BLACK	
SHELL	SHELL	SHIELD	

ITEM NO	PART	NAMES	QTY	REMARK
TEST CONDITION: LOW-VOLTAGE 15V				
INSULATION: UPON 1M ohm ELECTRIC CONDUCTION: INSIDE 1.5K ohm				
4		FERRITE: OD*1*ID=Ø11*20*5mm	2PCS	
3		CONNECTOR: MINI USB B5PM SHELL: GOLD-PLATING, BLACK INSULATOR, PIN: G/F	1PCS	
2		CONNECTOR: USB A MALE SHELL: GOLD-PLATING, BLACK INSULATOR, PIN: G/F	1PCS	
1		CABLE: USB2.0 28AWG*1P+28AWG*2C OD=Ø3.8±0.15mm COLOR: TRANSPARENT	1PCS	

PRODUCT	USB A MALE TO MINI B5PM	CUSTOMER	PCC	DRAWN	Y.M.X	THREE ANGLE PROJECTION
CUS.NO	70517	VERSION	1	CHECKED		
DR.NO		DRAWN DATE	2008.11.10	APPROVERD		